

### Standard Range Powdercoated Panel (Patented)



The **powdercoated panels** are part of the **CLOSING** product range. They are assembled with a bonding technique with a bi-component polyurethane glue which allows excellent mechanical properties and guarantees the quality.

Always seeking innovation, AV Composites developped a new panel for the manufacturing of aluminium shutters, doors and gates. It is made of a thermoplastic insulator and is the very first POWDERCOATED PANEL.

This insulating panel **saves** you a considerable amount of **manufacturing time**, allowing a rapid cut of the panel regardless of the shape. It also provides a powdercoated shutter at the same color of your window (european patent).

# AV Composites' panels, including the aluminium sandwich powdercoated panels, are protected by numerous patents!



ZA de la Massane 11 Av. des Joncades Basses 13210 Saint Rémy de Provence - FRANCE contact@avcomposites.com www.**avcomposites**.com Tel : +33 (0)4 32 61 92 95

Prizewinner of the 2010 INPI Innovation Trophies Prizewinner of the 2010 DELOITTE Technology Fast 50



100% recycled & 100% recyclable Infinite kinds of colors and aspects





Authorized Retailer



#### Standard Range Powdercoated Panel (Patented)



## Technical Specifications

Covering

3

**External and internal facing** Aluminium sheet (thickness 8/10th) with epoxy primer

Wainscoating effect Standard grooves' width: 85mm Other widths: contact us

2 Core of the panel Insulating core Thermoplastic,  $\lambda = 0.028$ 

(100% recycled & 100% recyclable)

- **Gluing** Polyurethane two-component adhesive
- 4 Thickness of finished panels Filling range: 25, 27, 28, 33mm Others: please contact us

5 Panels specifications Thermal loss coefficient

U = K = 1,03 (25) - 0,96 (27) - 0,93 (28) - 0,80 (33) W / K.m<sup>2</sup>

**Thermal Resistance R** R = 0,96 (25) - 1,03 (27) - 1,07 (28) 1,24 (33) K.m<sup>2</sup> / W

**Insulating foam fire resistance** M1 Quality, according to LNE N° P107497 certification

### 6 Dimensions - Weights

Width 1000 mm - 1200 - 1485mm Length 2440 à 7500 with steps of 250mm Weight 6,63 (25) - 6,79 (27) - 6,87 (28) 7,27 (33) kg/m<sup>2</sup>

### 7

Warranty Company Civil Insurance N° 2/700062



The installation of our systems must be made with the accossories of the AV Composites range. In case of dispute, the guarantees only apply if the user recommendations contained in our data sheets and Technical Notice, are met. Dark exterior color holding (such as: Slate) can not be guaranted in time. The advice and technical data refer to real informations and practical experiences. They are offered in good faith but without guarantee, since the conditions and methods of use are not under our control. We reserve the right to make change at any time without notice.